



Produktinformation

ARC Audio im Vertrieb von

RS Audio Vertriebsgesellschaft mbH

Gartenfelder Str. 29

13599 Berlin

Tel: 030 - 498 72 900

Fax: 030 - 498 72 929

arc-audio@rs-audio.com

www.rs-audio.de

Model

Specifications

Preis inkl. 19% MwSt.



Arc DXE

Digital X-Over with remote display
Microprocessor Controlled
Adressable F/R Ourputs
Full Sum Center Out
Two 12dB Bandpass X-Overs
Low Noise NE5532 IC's
Fully Balanced Controller Signal

€ 1820.-

ARC XEQ

7 Band equalizer with 12dB Boost/Cut
Subwoofer output with level control
Adjustable Subwoofer crossover
9 volts input
9 volts output

€ 360.-



ARC KEQ5

Five band equalizer with 12dB Boost/Cut.
5 volts output.
Sub out W/independent control.
Front panel adjustable Sub X-over.
Main/Aux input selector.
Universal half DIN chassis

€ 204.-



ARC IDX

2/3 Way Active Crossover
Front and Rear Inputs
Fully Adjustable Subsonic Filter
0-180 Variable Sub Phase
Front panel adjustable gains
24dB Sub Crossover

€ 292.-



ARC SRI

OEM Integration Module
Selectable RCA/Balanced Level output
AUX Input w/Remote level control
8 volt output
6 Channel Signal Summing
Balanced/Hi Level input

€ 292.-



ARC ALD

Selectable RCA/Balanced Level output (10 Volts)
RCA/Balanced speaker level input
Visual Gain matching interface

€ 128.-



Model

Specifications

Preis inkl. 19% MwSt.



2075 SE

2 Channels @ 4 Ohms
2 Channels @ 2 Ohms
2 Channels @ 1 Ohm
1 Channel @ 8 Ohms
1 Channel @ 4 Ohms
1 Channel @ 2 Ohms
Crossover Range
Bass Boost
Low Level Input Sensitivity
Balanced Input Sensitivity
High Level Input
Dimensions

100 Watts 24A
175 Watts 46A
150 Watts 50A
200 Watts 24A
350 Watts 47A
300 Watts 50A
30Hz - 550Hz (x10 300Hz - 550Hz)
0 - 15 dB @ 20 - 80Hz
.3V - 4V
.6V - 8V
NA
330x203x65 (L/B/H in mm)

€ 590.-



2150 SE

2 Channels @ 4 Ohms
2 Channels @ 2 Ohms
2 Channels @ 1 Ohm
1 Channel @ 8 Ohms
1 Channel @ 4 Ohms
1 Channel @ 2 Ohms
Crossover Range
Bass Boost
Low Level Input Sensitivity
Balanced Input Sensitivity
High Level Input
Dimensions

150 Watts 36A
300 Watts 73A
300 Watts 94A
300 Watts 34A
600 Watts 69A
600 Watts 95A
30Hz - 550Hz (x10 300Hz - 550Hz)
0 - 15dB @ 20Hz - 80Hz
.3V - 4V
.6V - 8V
NA
390x203x65 (L/B/H in mm)

€ 1080.-



2300 SE

2 Channels @ 4 Ohms
2 Channels @ 2 Ohms
2 Channels @ 1 Ohm
1 Channel @ 8 Ohms
1 Channel @ 4 Ohms
1 Channel @ 2 Ohms
Crossover Range
Bass Boost
Low Level Input Sensitivity
Balanced Input Sensitivity
High Level Input
Dimensions

330 Watts 72A
650 Watts 147A
650 Watts 184A
660 Watts 72A
1300 Watts 147A
1300 Watts 184A
30Hz - 550Hz (x10 300Hz - 5500Hz)
0 - 15dB @ 20Hz - 80Hz
.3V - 4V
.6V - 8V
NA
495x203x65 (L/B/H in mm)

€ 1520.-



4100 SE

4 Channels @ 4 ohms
4 Channels @ 2 ohms
4 Channels @ 1 ohm
2 Channels @ 8 ohms
2 channels @ 4 ohms
2 Channels @ 2 ohms
Crossover Range
Bass Boost
Low Level Input Sensitivity
Balanced Input Sensitivity
High Level
Dimensions

65 Watts 24A
110 Watts 42A
85 Watts 53A
130 Watts 30A
220 Watts 57A
145 Watts 53A
30Hz - 550Hz (x10 300Hz - 5500Hz)
0 - 15Db @ 20Hz - 80Hz
.3V - 4V
.6V - 8V
NA
390x203x65 (L/B/H in mm)

€ 1080.-



4200 SE

4 Channels @ 4 ohms
4 Channels @ 2 ohms
4 Channels @ 1 ohm
2 Channels @ 8 ohms
2 channels @ 4 ohms
2 Channels @ 2 ohms
Crossover Range
Bass Boost
Low Level Input Sensitivity
Balanced Input Sensitivity
High Level
Dimensions

110 Watts 50A
200 Watts 100A
200 Watts 116A
220 Watts 50A
400 Watts 101A
400 Watts 124A
30Hz - 55Hz (x10 300-5500Hz)
0-15dB @ 20Hz-80Hz
.3V - 4V
.6V - 8V
NA
495x203x65 (L/B/H in mm)

€ 1520.-



4000 SE

1 Channel @ 4 Ohms
1 Channel @ 2 Ohms
1 Channel @ 1 Ohms
Frequency response
Crossover Range
Bass Boost
Low Level Input Sensitivity
Balanced Input Sensitivity
Max Peak Current Draw
Idle Current
Dimensions

1200 watts
2300 watts
4000 watts
4Hz - 230Hz
30Hz - 230Hz
0dB - 15dB @ 20hz - 80hz
200mv - 4V
400mv - 8V
450A @ 1% Distortion
4 Amps
800x260x86 (L/B/H in mm)

€ 3400.-

Model

Specifications

Preis inkl. 19% MwSt..



KS 300.2

Power output RMS @ 4 ohms 2 X 180 watts
 Power output RMS @ 2 ohms 2 X 350 watts
 Power output RMS @ 4 ohms Bridged 1 X 700 watts
 Transient Distortion (100W) <.01% @ 4ohms
 Signal to Noise Ratio >98dB
 Bass Boost +18dB@45Hz
 Crossover (Butterworth) 55Hz-5.5KHz variable 12dB
 Size 335x203x60* (L/B/H in mm)
 * mit Logo 67mm

€ 450.-



KS 300.4

Power output RMS @ 4 ohms 4 X 90 watts
 Power output RMS @ 2 ohms 4 X 175 watts
 Power output RMS @ 4 ohms Bridged 2 X 350 watts
 Transient Distortion (100W) <.02% @ 4ohms
 Signal to Noise Ratio >95dB
 Bass Boost +18dB@45Hz
 Crossover (Butterworth) 55Hz-5.5KHz variable 12dB
 Size 345x203x60* (L/B/H in mm)
 * mit Logo 67mm

€ 510.-



KS 900.6

Power output RMS @ 4 ohms 4 X 60 watts
 Power output RMS @ 2 ohms 4 X 100 watts
 Power output RMS @ 4 ohms _(suwv) 2 X 155 watts
 Power output Bridged @ 4 ohms 2 X 120 watts
 Power output Bridged @ 4 ohms _(slv) 1 X 550 watts
 Transient Distortion (100W) <.01% @ 4ohms
 Signal to Noise Ratio >77dB
 Bass Boost +15dB@45Hz
 Crossover (Butterworth) 55Hz-5.5KHz var- 12dB
 Size 500x203x60* (L/B/H in mm)
 * mit Logo 67mm

€ 856.-



KS 500.1

Power output RMS @ 4 ohms 1 X 450 watts
 Power output RMS @ 2 ohms 1 X 600 watts
 Power output RMS @ 1 ohm 1 X 600 watts
 Transient Distortion (400W) <.05% @ 4 ohms
 S/N Ratio (A wtg.) >112dB
 Bass Boost +15dB@10-125Hz
 Crossover (Butterworth) 30Hz-250Hz variable 24dB
 Size 335x203x60* (L/B/H in mm)
 * mit Logo 67mm

€ 560.-



KS 1000.1

Power output RMS @ 4 ohms 1 X 850 watts
 Power output RMS @ 2 ohms 1 X 1000 watts
 Power output RMS @ 1 ohm 1 X 1000 watts
 Transient Distortion (400W) <.05% @ 4 ohms
 S/N Ratio (A wtg.) >112dB
 Bass Boost +15dB@10-125Hz
 Crossover (Butterworth) 30Hz-250Hz variable 24dB
 Size 390x203x60* (L/B/H in mm)
 * mit Logo 67mm

€ 720.-

Model

Specifications

Preis inkl. 19% MwSt..



KS125.2 Mini

Power output RMS @ 4 ohms	2 X 70 watts
Power output RMS @ 2 ohms	2 X 125 watts
Power output RMS @ 4 ohm	1 X 250 watts
THD	>.05% @ 4 ohms
S/N Ratio (A wtg.)	>111dB
Bass Boost	+15dB@45Hz
Crossover (Butterworth)	55Hz-550Hz 12dB
Size	215x124x45 (L/B/H in mm)

€ 248.-



KS125.4 Mini

Power output RMS @ 4 ohms	4 X 75 watts
Power output RMS @ 2 ohms	4 X 125 watts
Power output RMS @ 4 ohm	2 X 250 watts
THD	<.05% @ 4 ohms
S/N Ratio (A wtg.)	>109dB
Bass Boost	+15dB@45Hz
Crossover (Butterworth)	55Hz-550Hz 12dB
Size	310x132x45 (L/B/H in mm)

€ 348.-



KS500.1 Mini

Power output RMS @ 4 ohms	1 X 300 watts
Power output RMS @ 2 ohms	1 X 500 watts
THD	<.05%
S/N Ratio (A wtg.)	>82dB
Bass Boost	+15dB@45Hz
Crossover (Butterworth)	30Hz-200Hz 24dB
Size	310x132x45 (L/B/H in mm)

€ 348.-

Alle Lieferungen innerhalb der Bundesrepublik Deutschland werden ohne zusätzliche Versandkosten an Sie versendet.

Zahlungen für bestellte Waren können per Vorkasse, Paypal oder auch per Nachnahme erfolgen.

Für eine Zahlungsweise per Nachnahme sind zusätzlich EUR 10,- Gebühren zu bezahlen.

Die Preise haben bis zum Erscheinen einer neuen Preisliste Gültigkeit.

Technische Änderungen vorbehalten. Stand 14.06.2010

RS Audio Vertriebsgesellschaft mbH